

**BUILT TOUGH,  
EASY TO  
SERVICE**



**STRIKE FIRST**  
FIRE EXTINGUISHERS

**WHEN  
SECONDS  
COUNT.**



**Manufacturing Fire Equipment  
for over 35 Years**

[info@strike-first.com](mailto:info@strike-first.com) | [strike-first.com](http://strike-first.com)



**MULTI-PURPOSE**  
**ABC DRY CHEMICAL**



A



B



C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)
- 90% MAP (mono ammonium phosphate powder)



**MEETS OR EXCEEDS**  
ANSI/UL 299 & 711



**MEETS OR EXCEEDS**  
CAN/ULC-S504 & S508

CAPACITY	2.5 lbs	5 lbs	5 lbs	10 lbs	20 lbs	30 lbs
Model No.	SF-ABC110ST	SF-ABC310	SF-ABC340	SF-ABC680	SF-ABC1020	SF-ABC30
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C



**REGULAR**  
**BC DRY CHEMICAL**



B



C

- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)



**MEETS OR EXCEEDS**  
ANSI/UL 299 & 711



**MEETS OR EXCEEDS**  
CAN/ULC-S504 & S508

CAPACITY	2.75 lbs (1.2 kg)	5 lbs (2.3 kg)	10 lbs (4.5 kg)	20 lbs (9.1 kg)
Model No.	SF-SB275	SF-SB5	SF-SB10	SF-SB20
UL/ULC Rating	10-B : C	10-B : C	60-B : C	80-B : C



**CO<sub>2</sub>**  
**CARBON DIOXIDE**



B



C

- Well suited for corrosive environments
- Super durable polyester powder paint finish with superior corrosion resistance
- Industrial strength aluminum cylinder
- Stainless steel handles, pull pin and retaining chain
- Chrome plated solid brass valve
- Strong impact resistant horn
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- D.O.T. approved cylinder
- U.S.C.G. approved with bracket listed on label
- Temperature range: -22°F to 120°F (-30°C to 49°C)



**MEETS OR EXCEEDS**  
ANSI/UL 299 & 711



**MEETS OR EXCEEDS**  
CAN/ULC-S504 & S508

CAPACITY	5 lbs (2.3 kg)	10 lbs (4.5 kg)	15 lbs (6.8 kg)	20 lbs (9.1 kg)
Model No.	SF-5C02	SF-10C02	SF-15C02	SF-20C02
UL/ULC Rating	5-B : C	10-B : C	10-B : C	10-B : C



## WATER



5 YEAR WARRANTY



A

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Shipped empty without pressure
- Schrader valve for pressurizing
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

<b>CAPACITY</b>	<b>2.4 gallons (9 litres)</b>
<b>Model No.</b>	SF-PW250
<b>UL/ULC Rating</b>	2-A



LISTED  
**MEETS OR EXCEEDS**  
ANSI/UL 299 & 711



LISTED HOMOLOGUE  
**MEETS OR EXCEEDS**  
CAN/ULC-S504 & S508



## WET CHEMICAL



5 YEAR WARRANTY



A



K

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Factory filled and pressurized
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 35°F to 120°F (2°C to 49°C)

<b>CAPACITY</b>	<b>1.6 gallons (6 litres)</b>
<b>Model No.</b>	SF-6LK
<b>UL/ULC Rating</b>	1-A : K



LISTED  
**MEETS OR EXCEEDS**  
ANSI/UL 299 & 711



LISTED HOMOLOGUE  
**MEETS OR EXCEEDS**  
CAN/ULC-S504 & S508



## DRY CHEMICAL

## AUTOMATIC HEAT ACTUATED MULTI-PURPOSE



A



B



C

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- UL Listed Heat Activated Sprinkler Head, rated at 165 degrees F (74° Celsius)
- Meets D.O.T. Requirements
- Designed to provide supplementary fire protection
- Available in two mounting styles: horizontal and vertical
- Disposable unit, does not require maintenance and inspection at 6 or 12 years
- Typical installation locations: specific fire risk areas such as flammable liquid storage rooms, construction trailers and manufacturing process areas i.e. paint booths

<b>CAPACITY</b>	<b>2.5 lbs (1.13 kg)</b>	<b>5 lbs (2.3 kg)</b>	<b>10 lbs (4.5 kg)</b>	<b>20 lbs (9.1 kg)</b>
<b>Model No.</b>	SF-AFE2.5ABCV	SF-AFE5ABCV	SF-AFE10ABCV	SF-AFE20ABCV
	SF-AFE2.5ABCH	SF-AFE5ABCH	SF-AFE10ABCH	SF-AFE20ABCH



### FIRE EXTINGUISHER CLASS LEGEND:



**A** WOOD, PAPER, CLOTH



**B** FLAMMABLE LIQUIDS & GASES



**C** ELECTRICAL EQUIPMENT



**K** RESTAURANT, KITCHEN HAZARD



# FIRE EXTINGUISHER VEHICLE/MARINE BRACKETS

## STANDARD DUTY



MODEL	UP2, UP2 - DB	UB5, UB5 - DB
For Extinguisher	2.5 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Stainless steel strap and clips
- Durable rubber bumpers

## MEDIUM DUTY



MODEL	UP10 - MD	UP5 - MD
Diameter	5 1/8" (13 cm)	4 1/4" (11 cm)
For Extinguisher	10 lb Dry Chemical	5 lb Dry Chemical
U.S.C.G. Approved	YES	YES

- Durable polyester powder paint finish
- Heavy gauge steel construction
- Compact design
- Ideal for forklifts, industrial trucks and delivery vehicles
- Double Strap Available

## HEAVY DUTY



MODEL	HDVB-1	HDVB-2	HDVB-3	HDVB-4
Diameter	4 - 4 3/4" (102 - 121 cm)	5 - 6" (127 - 152 cm)	6 1/4 - 7 1/8" (159 - 181 cm)	6 1/4 - 7 1/8" (159 - 181 cm)
For Extinguisher	5 lb ABC/BC	10 lb ABC/BC 5 lb CO <sub>2</sub>	20 lb ABC/BC 10 lb CO <sub>2</sub> 15 lb CO <sub>2</sub>	30 lb ABC
U.S.C.G. Approved	YES	YES	YES	YES

- Strong Uni-Body Construction
- Reflective label for added safety
- Stainless steel pull pin with tether
- Rounded corners for added safety
- Durable polyester powder coat finish
- Individually boxed for easy handling

## WALL HOOKS



TYPE	PART NO.	FOR MODEL(S)
Dry Chemical	C160739	5 lb ABC/BC
	C160753	10 lb ABC/BC
	C160793	20 lb ABC/BC
	C160794	30 lb ABC/BC
CO <sub>2</sub>	SF5WH	5 lb CO <sub>2</sub>
	SF1015WH	10 lb CO <sub>2</sub>
		15 lb CO <sub>2</sub>
Class K Water	W160600	1.6 gal (6L) Class K
		2.4 gal (9L) Water

- Heavy gauge steel construction
- Designed for easy removal of fire extinguisher
- Durable polyester powder coat finish
- Universal design



## EXTINGUISHER CART



MODEL	CAPACITY	HEIGHT	WIDTH	DEPTH	WEIGHT
HD-CART	7 - 8" Diameter	39" (99 cm)	13 1/4" (34 cm)	13 1/2" (8.2 cm)	20 lb (9 kg)



Shown with 30 lb ABC