

MULTI-PURPOSE ABC DRY CHEMICAL



STRIKE FIRST
FIRE EXTINGUISHERS



**WHEN
SECONDS
COUNT.**



Built Tough and Ready to Serve

- Modified universal valve body
- Accepts both pin or fork wall hooks
- Steel cylinder
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)
- 90% MAP (mono ammonium phosphate powder)

**STRIKE FIRST ABC Multi-Purpose
Dry Chemical Fire Extinguishers
are designed for:**



A WOOD
PAPER
& CLOTH



C ELECTRICAL
EQUIPMENT



B FLAMMABLE
LIQUIDS
& GASES



MEETS OR EXCEEDS:
ANSI/UL 299 & 711



**LISTED
HOMOLOGUÉ**

MEETS OR EXCEEDS:
CAN/ULC-S504 & S508



Manufacturing
Fire Equipment
for over 35 Years



CAPACITY	2.5 lbs	5 lbs	5 lbs	10 lbs	20 lbs	30 lbs
Model No.	SF-ABC110ST	SF-ABC310	SF-ABC340	SF-ABC680	SF-ABC1020	SF-ABC30
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C
U.S.C.G. Approval	Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size II	Type A Size II, Type B:C Size III	Type A Size II, Type B:C Size IV
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)
Discharge Time	9 sec	14.5 sec	14.5 sec	21 sec	28 sec	28 sec
PSI	150	195	195	235	235	195
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	16 7/8" (43 cm)	21 1/4" (54 cm)	24" (61 cm)	30 3/4" (78 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)	7 1/8" (18 cm)
Weight	4 1/2 lb (2 kg)	10 1/2 lb (4.8 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)	50 1/3 lb (22.8 kg)
Chrome Option	YES	YES	YES	-	-	-
Standard Bracket	Wall or Vehicle/ Marine	Wall or Vehicle/ Marine	Wall or Vehicle/ Marine	Wall or Vehicle/ Marine	Wall	Wall
Optional Brackets	Wall UP2 UP-DB	UB5 UB5-DB UP5-MD HDVB-1	UB5 UB5-DB UP5-MD HDVB-1	UP-10MD HDVB-2	HDVB-3	HDVB-4 HD-CART



STRIKE FIRST
FIRE EXTINGUISHERS

777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767 TF 1 888 575-1132

info@strike-first.com | www.strike-first.com